




KEY SWITCH






Technical Data

Rated Insulation Voltage	600V
Contact resistance	≤50mΩ
Rated thermal current I _{th}	10A
Switch rating	AC-15 - U _e : 380V/250V, I _e =4.5A ; DC-13 - U _e : 380V/250V, I _e =4.5A
Ambient temperature	Operating: -25 to +70°C
Humidity	≤90%
Recommended torque	0.9Nm
Contactable Area	1x0.5m m ² (min), 2x1.5m m ² or 1x2.5m m ²
Service life	Mechanical - 1,000,000 operations min. Electrical - 100,000 operations min.
Protection degree	IP65
Size of moulding hole	Φ22mm

TWO-POSITION

	Latching 	Momentary from R to L Spring Return 	Contact Type	
	ADP2 BG21	ADP2 BG41		1NO
	ADP2 BG21	ADP2 BG42		1NC
	ADP2 BG25	ADP2 BG45		1NO+1NC

THREE-POSITION

	Latching 	Momentary from L to C, from R to C Spring Return 	Momentary from L to C Spring Return 	Momentary from R to C Spring Return 	Contact Type	
	ADP2 BG33	ADP2 BG53	ADP2 BG63	ADP2 BG73		1NO+1NO
	ADP2 BG35	ADP2 BG55	ADP2 BG65	ADP2 BG75		1NO+1NC

Outline and Dimension(mm)

